



PROJECT	DATE
TYPE	QTY


# Indoor Series IMP-8000











Right Side View

## Left Side View

## **80W INDOOR FIBER OPTIC LED ILLUMINATOR**

#### **DESCRIPTION:**

The **IMP-8000** is the indoor version of the ION-8000 designed for architectural illumination, and pool or fountain applications. High-power white LEDs provide consistent color temperature and higher light output and longer life than conventional 150-watt fiber optic illuminator bulbs.

Slow-rate controlled dimming and shielded conductors keep the driver's EMI emissions at a very low level.

IMP-8000 Series LED Light Sources have a 5RPM (top speed) motor than can be speed controlled via DMX or a manual speed control with an attached sparkle wheel for added effects.

The Impact Lighting Inc. Sync® module creates turbulent, pulsated air-jets that can be directed precisely to locations where thermal management is needed. A patented actuator technology delivers robust thermal management.

#### **FEATURES:**

- USITT DMX512A- and IMP-5000 Sync-compatible
- Isolated DMX or RS232 IN/OUT No "Y" Connection
- · Accurate, smooth dimming and high-res color mixing
- · Drive, control and thermal protection per fixture
- · Easy networking

## **SPECIFICATIONS:**

Input Voltage	120 - 240 VAC
Amps	0.8 Max (on white)
Wattage	80 - 90W Max (on white)
Hz	50 / 60
Fiber Capacity	1000
Operating Temp	-10° C to 50° C
Weight	9lbs.

## **PHOTOTMETRICS:**

WW	2560 LM
CW	4400 LM
RGBW	3465 LM (R=765 G=920 B=230 W=1550

ORDERING | Example: IMP-8000 - WW - S - DMX - T2 IMP-8000, 3000K LED Engine, with Sparkle Wheel, with DMX Effects control and Toggle Control System

MODEL	LED ENGINE	EFFECTS	EFFECTS CONTROL	LED CONTROL SYSTEM
IMP-8000 -				
80W LED IP-20 (INDOOR rated)	<b>WW</b> - 3000K <b>CW</b> - 5500K	N - None* S - Sparkle Wheel	N - None DMX - DMX	N - None DMX - DMX 512*
Fiber Optic Light Source	<ul><li>B - Blue</li><li>RGBW - Red/Green/Blue/White</li><li>D - Dynamic White 3000-5000K</li></ul>	F - Color Filter  * If NONE is selected you can not have an effects control option	MAN - Manual RS232- Serial Control	T2 - Toggle Control  RS232- Serial Control*  *Not needed if single color

5.25"

### IMPACT LIGHTING INC.